

TRANSMISSIONS & POKER HEADS

PENDULUM





The TNR Transmissions and ANR poker heads from ENAR provide the absolute optimal compaction of concrete, making it easier and quicker to vibrate the concrete to a high quality. The range is also provided with a variety of couplings which connect to electric, petrol and diesel motors.

Assured Range
Every need is covered by ENAR as the ANR/TNR series ranges from 25mm to 75mm poker heads and 4m to 9m transmissions.



**GASOLINE/
DIESEL/
ELECTRIC**



+ Cost Effective
And quality assured

The TNR/ANR range is cheaper than the High frequency range but offers all the quality in the finish of the concrete vibrated.

+ Adapts to the job!
No matter the job.

The TNR/ANR range adapts using its wide range of sizes and lengths which can all be connected to Electric, Petrol and Diesel motors.

+ Robust and Durable
Made to last.

The ANR pokers are available with a rubber tip to increase the durability and is also well protected against damage by the mechanical system

TECHNICAL DATA

POKER HEADS ANR

MODEL	DIAMETER (mm)	LENGTH (mm)	WEIGHT (Kg)	SPEED (r.p.m)	PERFORMANCE (m ³ /h)	TRANSMISSIONS
ANR25	25	350	1.2	16,000	10	TNR4-25/TNR6-25
ANR38	38	375	2.5	12,000	15	TNR4-38/TNR6-38
ANR48	48	445	4.3	12,000	25	TNR4-48/TNR6-48
ANR58	58	450	6.4	12,000	30	TNR4-58/TNR6-58
ANR70	70	510	7.5	12,000	35	TNR4-70/TNR6-70

- › Axle rotates at 3,000RPM with the Pendular system reaching 12,000RPM.
- › Wide range of connections.

TRANSMISSIONS TNR

MODEL	LENGTH (mm)	WEIGHT (Kg)
TNR4-25	4	6
TNR6-25	6	8
TNR4-38	4	11.1
TNR6-38	6	15.8
TNR4-48	4	11.1
TNR6-48	6	15.8
TNR4-58	4	11.1
TNR6-58	6	15.8
TNR4-70	4	11.1
TNR6-70	6	15.8



- › Poker end of the transmission is vulcanized for poker heads 48, 58 and 70mm.
- › High quality transmission hose, 26mm diameter (ANR25) and 36mm (all other sizes):
- › Different couplings available on request.

