

SINGLE DIRECTION VIBRATING COMPACTOR ZEN





The ENAR ZEN single direction vibrating compactor Series are economical, easy to handle and can easily be transport.

The Enar Zen series are users' number one choice for compacting mixed soil in restricted areas, cohesive materials and paving stones.

Variety and Efficiency.


The Enar Zen Series offers a range up to 100kg with different engine configuration and options according to the needs of each client.

The Robust and ergonomic handle, the incorporation of wheels to the plate makes it easy to transport to any desired location on the construction site.



+ Transportation easy.

With the incorporation of a wheel set, we've made it easier than ever to transport vibrating plates at the construction site.



+ Full range A variety of models.

The single direction vibrating compactor comes in a complete range of engines for the needs of each client.

+ Robust Resistant.

The base of the Enar Zen Series is made of high quality resistant cast iron to provide a long lasting operational life. It also comes with a heavy duty frame that protects the engine.



+ Ergonomics of use.

The handle is completely foldable on the compactor plate and it included as vibration absorption system to a higher comfort users.

TECHNICAL DATA

MODEL	WEIGHT WITHOUT FUEL (Kg)	CENTRIFUGAL FORCE (N)	SPEED (m/min)	DIMENSIONS (WidexLongxHigh)	ENGINE
ZEN 16CG	90	16,000	0-22	430x1165x958	HONDA GX 160 CE HONDA GX 160 ENAR G 160F ROBIN SUBARU EX17 CE
ZEN 16DG	94	16,000	0-22	500x1165x958	
ZEN 20CG	91	20,000	0-23	430x1165x958	
ZEN 20DG	95	20,000	0-23	500x1165x958	
ZEN 16CD	106	16,000	0-22	430x1165x958	HATZ 1B 20
ZEN 16DD	110	16,000	0-22	500x1165x958	
ZEN 20CD	107	20,000	0-23	430x1165x958	
ZEN 20DD	111	20,000	0-23	500x1165x958	

- › Vibration frequency : 5,600 vib/min.
- › Accelerator integrated in handle.
- › Centrifugal clutch driven and easy start.
- › Option of polyurethane sheet for the base plate, for works on paving stones.
- › Option of a 9-liter tank capacity is suitable for both asphalt works and dusty environment. It is easily removable for filling.

