

PORTABLE PETROL VIB-BAR



The **VIB-BAR** from ENAR is a simple but effective set up consisting of a motor, aluminium bar with a handle, a short flexible shaft and a poker. As always.

No Restriction Of Movement.

The **VIB-BAR** provides the user with maximum freedom of movement. No electric cables, no pieces to pull along the floor, everything held on your shoulder and controlled using both hands. This product has been designed primarily for the user's comfort and ability to move around the job site with ease. It is ideal for working on pavements and between rebar.



+ No surprise shocks!

Added safety for the user and work colleagues.

Thanks to its petrol motor, no plugs or electric cables are used on this product. This means no tripping over loose cables, no exposed damaged or exposed wires and no risk of electric shock.

+ Super Light

No overbearing back aches.

As well as being light thanks to its simple design, the **VIB-BAR** is also very compact while in use and even more so when disassembled to be stored away. Another reason why the product provides the user with exceptional movement across the jobsite.

+ Independence!

No need to fight for a plug socket!

Thanks to its light and compact design as well as running on petrol, this product provides independence to the user. No need to work within the area permitted by the length of the electric cable, no need to pay extra attention to cables knotting or tripping people up and no need to share due to the limited plug sockets. Start up the motor and walk wherever the job requires to be.

TECHNICAL DATA

MODEL	WEIGHT (Kg)	POWER (CV)	ENGINE	FUEL	ENGINE CAPACITY CC	SPEED (r.p.m)
VIB-BAR H	6	1,6	HONDA GX 35 4T	GASOLINE unleaded Petrol	35,8	10.000

- › Centrifugal clutch.
- › Throttle integrated into the handle.

AX HEADS

MODEL	DIAMETER (mm)	LENGTH (mm)	WEIGHT (Kg)	SPEED (r.p.m)	PERFORMANCE m ³ /h
AX 45	45	325	3	9.500	25



- › Oversized eccentric.
- › 4 oil lubricated bearings with double lock retention.
- › Multiple poker heads available but will reduce the performance of the equipment

FLEXIBLE TRANSMISSIONS

MODEL	LENGTH (m)	WEIGHT (Kg)
TBX 0,5	0,5	2



- › High quality, reinforced transmission.
- › The exterior of the transmission is supported by a flexible metal coil.

